



2 - 10mm 3D Wire Forming Machine High Precision Fixed head

Our Product Introduction


Basic Information

- Place of Origin: Guangdong, China
- Brand Name: Jin Hongxiang
- Certification: CE
- Model Number: JX3D2-8
- Minimum Order Quantity: 1 set
- Price: consult
- Packaging Details: Export wooden case
- Delivery Time: 5-10 days or negotiation
- Payment Terms: L/C, T/T
- Supply Ability: 20 Set/Sets per Month



Product Specification

- Product Name: 3D Wire Bending Machine
- Machine Type: 3D
- Control System: PLC+servo
- Applicable Industries: Hardware, wire Processing
- Warranty Of Core Components: 1 Year
- Wire Size: ϕ 2-8mm
- No. Of Axis: 7 Axis
- Highlight: 3D Wire Bending Machine
- Automation: Automatic
- Port: Shenzhen
- Highlight: **3D Wire Forming Machine High Precision, 10mm 3D Wire Forming Machine**



Product Description

3D Wire forming machine 2-10MM

This 3D molding machine is for iron wire with a diameter of 2-10mm

The biggest feature of this machine is that the iron wire rotates and the head is fixed

Performance characteristics

1. The computer starts and shuts down quickly, and the operation is simple and convenient. The computer interface can change the program while adjusting speed while producing.
2. High brand high-speed motor and reducer are used in configuration, and the production speed is more than 25% higher than that of similar products in domestic peers.
3. The production can realize that the angle does not change at the slowest angle, and the production stability is better.
4. Bearings, gears and other important parts are imported brand accessories, with a 365 day warranty, and the equipment is durable and reliable.
5. With high precision, it can be used for wire rod forming products in the range of 2.0-10 mm wire diameter, and the error is reduced to 0.1 mm
6. The matching use of steel wire butt joint machine makes the wire change operation of the machine more convenient.
7. It can be connected to the Internet and WiFi through mobile phone or computer to realize remote control, which makes after-sales service more convenient.

Technical Parameters

Model	JX3D-6	JX3D-8	JX3D-10
No. of axis	380V,7 axis	380V,7 axis	380V,7 axis
Machining wire diameter(MM)	Hard material $\Phi 2.0$ $\Phi 4.0$ Soft material $\Phi 2.0$ $\Phi 6.0$	Hard material $\Phi 3.0$ $\Phi 6.0$ Soft material $\Phi 3.0$ $\Phi 8.0$	Hard material $\Phi 3.0$ $\Phi 8.0$ Soft material $\Phi 3.0$ $\Phi 10.0$
Number of wire feeding wheels	3 groups	3 groups	3 groups
Spool servo motor (KW)	2	2.7	4.5
Head shaft servo motor (KW)	2	2.7	4.5
Cutter shaft servo motor(KW)	1	1	2
Lifting shaft servo motor (KW)	1	1	2
Angle axis servo motor (KW)	1	1	1
Machine size (MM)	3800X1860X1660	3800X1860X1660	3800X1860X1660

1. Computer control,
 - A. adopt speed closed-loop control; The maximum pulse frequency can reach 2MHz.
 - B system design integrated motherboard and IO board integrated design, simple wiring and simple installation.
 - C system is equipped with windows interface development. The operation interface is simple and fashionable. Like the operation mode of ordinary computers, the mouse and keyboard are used together to replace the traditional key operation, so as to reduce the risk of key aging and failure.
 - D. the speed can be modified at any time in the production process, which is easy to operate.



3D bending product display





Dongguan Jinghongxiang Automation Equipment Co., Ltd.



13925780098



jhx16888@gmail.com



wire-bendingmachine.com

No. 78, Shangzhong Road, Shangdi Industrial Zone, Liaobu Town, Dongguan, Guangdong, China